

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (original) An electronic device, comprising:
 - a processor;
 - an output device connected to the processor for issuing a stimulus to a user of the electronic device;
 - at least one input device connected to the processor and responsive to user input activity; and
 - a device lock module associated with the processor for (i) implementing restrictions on user access to the electronic device if user input activity falls below a threshold; and (ii) redetermining the threshold if a stimulus is issued by the output device.
2. (original) The electronic device of claim 1 wherein the threshold includes a lack of user input activity within a timed period, the device lock module configured for redetermining the timed period if the stimulus is issued by the output device within the timed period.
3. (original) The electronic device of claim 2 wherein the device lock module is configured for setting an initial value for the timed period; monitoring for user input activity within the timed period and if user input activity is not detected within the timed period then implementing the restrictions on user access; and monitoring for issuance of the stimulus within the timed period and if the stimulus is issued during the timed period, resetting a time remaining in the timed period to a second value less than the initial value.

4. (original) The electronic device of claim 3 wherein if the stimulus is issued during the timed period the time remaining in the timed period is reset to the second value only when the time remaining in the timed period when the stimulus is issued exceeds the second value.
5. (original) The electronic device of claim 3 wherein the device lock module is configured for tracking user response times to issued stimuli and adjusting the second value based on the tracked user response times.
6. (original) The electronic device of claim 1 wherein the stimulus includes at least one of an aural stimulus and a physical stimulus.
7. (original) The electronic device of claim 1 wherein the electronic device is a mobile communications device enabled for communications over a wireless network, and the processor is configured for causing the output device to issue the stimulus when the electronic device receives a new communication addressed to it over the wireless network.
8. (original) The electronic device of claim 7 wherein the new communication is selected from the group consisting of an electronic message and an incoming telephone call.
9. (original) The electronic device of claim 1 wherein the electronic device includes an event scheduling application associated with the processor for generating event reminders, the processor being configured for causing the output device to issue the stimulus when an event reminder is generated.
10. (original) The electronic device of claim 1 wherein stimulus are issued for at least two different types of events, the threshold being redetermined based on the type of event for which the stimulus is issued.

11. (original) A method for providing security for a mobile communications device, including steps of:

monitoring for predetermined user interaction with the mobile communications device;

locking the mobile communications device if the predetermined user interaction is not detected within a predetermined lockout time interval; and

resetting the lockout time interval to a shorter value if a user stimulus is issued by the mobile communications device.

12. (currently amended) The method of claim 11 wherein [[in]] the resetting step is performed based on if a time remaining in the lockout time interval is greater than the shorter value.

13. (original) The method of claim 11 including monitoring for new communications received by the mobile communications device and issuing the user stimulus in response to receiving a new communication at the mobile communications device.

14. (original) The method of claim 11 including monitoring a length of time for user interaction to occur after the user stimulus has been issued and adjusting the shorter value based thereon.

15. (currently amended) A mobile device, comprising:

a processor;

at least a first input device connected to the processor for providing input signals thereto; [[and]]

at least one user input device connected to the processor and having a physical user interface responsive to user input activity;

an output device connected to the processor for providing output to a user of the mobile device;

the processor being configured for determining location information for the mobile device based on input signals received from the first input device ~~and adjusting an operating characteristic of the electronic device based on the determined location information;~~ and

a device lock function associated with the processor for implementing restrictions on user access to the mobile device if user input activity for the mobile device falls below a threshold, the device lock function being configured for requiring a predetermined user input through the at least one user input device to remove the restrictions on user access once they have been implemented, the device lock function being configured for changing the predetermined user input required to remove the restrictions on user access in dependence on the determined location information.

16. (cancelled)

17. (cancelled)

18. (currently amended) The mobile device of claim [[17]] 15 wherein the predetermined user input includes entry of a predetermined password, the device lock function being configured for selecting which of a plurality of predetermined passwords is security-setting ~~determines which of a plurality of predetermined passwords is required to be used as the predetermined user input to the mobile device~~ required to remove the restrictions on user access in dependence on the determined location information.

19. (currently amended) The mobile device of claim [[16]] 15 wherein the ~~security-setting determines the threshold~~ device lock function is configured for determining the threshold in dependence on the determined location information.

20. (currently amended) The mobile device of claim ~~[[16]]~~ 15 wherein the first input device includes an interface for docking the mobile device to a desktop computer, the location information being determined based on whether the mobile device is docked to the desktop computer.

21. (original) The mobile device of claim 20 wherein the security setting of the device lock function is set to mirror that of the desktop computer when the mobile device is docked to the desktop computer.

22. (currently amend) The mobile device of claim ~~[[16]]~~ 15 wherein the first input device includes a GPS receiver.

23. (currently amend) The mobile device of claim ~~[[16]]~~ 15 wherein the first input device includes a wireless communications subsystem connected to the processor for exchanging communications signals with a wireless network including a plurality of base stations, the location information being determined based on identities of the base stations.

24. (currently amended) The mobile device of claim 15 wherein the mobile device is enabled for receiving electronic messages and includes a message filtering module associated with the processor for filtering electronic messages received by the mobile device, the message filtering module being configured for changing operating characteristic including filtering criteria for filtering the electronic messages in dependence on the determined location information.

25. (currently amended) A method for providing security to a mobile electronic device having a device lock function that restricts use of the mobile electronic device by a user thereof by locking the device under predetermined circumstances, the method including steps of:

receiving input signals from an input device of the mobile electronic device;

determining if the mobile electronic device is in a secure location based on the input signals; and

~~applying a first security setting to requiring input of a first predetermined password by a user to unlock~~ the mobile electronic device if it is in the secure location and ~~applying a second security setting to requiring input of a second predetermined password by a user to unlock~~ the mobile electronic device if it is not in the secure location.

26. (currently amended) A method for providing security to a mobile electronic device having a device lock function that restricts use of the mobile electronic device by a user thereof by locking the electronic device when user interaction with the mobile device falls below a threshold, the method including steps of:

receiving input signals from an input device of the mobile electronic device;

determining if the mobile electronic device is in a secure location based on the input signals; and

applying, if the mobile electronic device is determined to be in a secure location, The method of claim 25 wherein the first security setting specifies a first countdown timer value within which defining a duration after which the mobile electronic device will be locked if user interaction with the mobile electronic device is not detected, and the second security setting specifies applying, if the mobile electronic device is determined not to be in a secure location, a second, shorter, countdown timer value within which defining the duration after which the mobile electronic device will be locked if user interaction with the mobile electronic device is not detected.

27. (cancelled)

28. (new) A mobile device enabled for receiving electronic messages, comprising:

a processor;

at least a first input device connected to the processor for providing input signals thereto;

an output device connected to the processor for providing output to a user of the mobile device;

the processor being configured for determining location information for the mobile device based on input signals received from the first input device; and

a message filtering module associated with the processor for filtering electronic messages received by the mobile device, the message filtering module being configured for adjusting filtering criteria for filtering the electronic messages in dependence on the determined location information.